



AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

Applicant:	Bayco Products, Inc.	Manufacturer:	Far East Lighting Co., Ltd.
Address:	640 South Sanden Boulevard Wylie, TX 75098	Address:	Sanbei Cixi Ningbo 315331
Country:	USA	Country:	China
Contact:	Jim Conner	Contact:	Judy Huang
Phone:	469-326-9452	Phone:	0086-574-63739017
FAX:	469-326-9402	FAX:	0086-574-63739015
Email:	jconner@baycoproducts.com	Email:	fe2@fareastlamp.com

Party Authorized To Apply Mark: Same as Manufacturer
Report Issuing Office: Dallas.TX

Control Number: 4002026 **Authorized by:** *Patricia Starr*
William T. Starr, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.
165 Main Street, Cortland, NY 13045
Telephone 800-345-3851 or 607-753-6711 Fax 607-756-6699



AUTHORIZATION TO MARK

Intrinsically Safe Apparatus and Associated Apparatus for Use in Class I, II & III, Division 1, Hazardous (Classified) Locations (ANSI/UL 913-2011, Seventh Ed., Issued July 31, 2006, Revised September 23, 2011);

Intrinsically Safe and Non-incendive Equipment for Use in Hazardous Locations (CAN/CSA-C22.2 No. 157-92 (R2012), Third Edition, Issued June 1992, with Update No. 2, June 2003);

Enclosures for Use in Class II Groups E, F & G Hazardous Locations General Instruction No 1 (CSA C22.2 No. 25-1966 (R2009), Issued September 1966);

Standard(s): Explosive Atmospheres – Part 11: Equipment Protection by Intrinsic Safety "i" (ANSI/UL 60079-11-2011, Fifth Ed., Issued September 30, 2009, Revised May 5, 2011);

Explosive atmospheres – Part 0: Equipment – General requirements (ANSI/UL 60079-0-2009, Fifth Ed., Issued October 21, 2009, Revised December 8, 2009);

Explosive atmospheres — Part 11: Equipment protection by intrinsic safety "i" (CAN/CSA-C22.2 No. 60079-11:11, First Ed. , Issued December 2011);

Explosive atmospheres — Part 0: Equipment — General requirements (CAN/CSA-C22.2 No. 60079-0:11, Second Ed., Issued December 2011)

Portable LED Flashlight and/or Floodlight

Product: For Use In: Class I, Division 1, Groups A, B, C & D; Class II, Division 1, Groups E, F & G; Class III; Class I, Zone 0; and Zone 20 Hazardous (Classified) Locations
Protection Method: AEx ia IIC T3 Ga and Ex ia IIC T3 Ga; AEx ia IIIC T165°C Da
Temperature Code: T3
Ambient Temperature Range: -20 °C (-4 °F) to +40 °C (+104 °F)

Brand Name: Nightstick

Models: XPP-5420 and XPP-5422. May be followed by B or G.